



Laminated Floor Shine

Product Data sheet

Type	Metallised acrylic emulsion, specially formulated for laminated flooring. Leaves a brilliant shine without buffing.
Intended Use	To restore shine (gloss) to all types of laminated flooring..
Special Features	Low odour. Easy application. Quick drying, no need to buff. Wash equipment in water. Conforms to Safety of Toys Regulations BS EN Part 3 1995 .
Preparation	The floor must be clean, dry and free from dust. If at any time wax polish has been applied it must be removed using steel wool and white spirit, wiping away the solution formed with a clean rag whilst still damp.
Application	Apply evenly with a mop or cloth and allow to dry. Dries to a brilliant shine, no buffing required. For improved durability a second coat may be applied after 24 hrs.
Coats	1 or 2 as required, depending on the level of traffic.
Drying Time	10-20 minutes.
Re-coating Time	24 hours.
Application Temp.	Ideally 15-25°C.
Coverage	Approximately 14 sq.m per litre, 1 coat.
Maintenance	Sweep regularly with a soft broom and clean with a damp cloth. Re-coating will be required at regular intervals. Before re-coating clean with water and detergent but after six or seven coats have been applied, the Floor shine should be removed.
Compatibility	Remove surface grime with detergent and water. When dry, make a solution of 250ml household ammonia with 3 Litres cold water and apply liberally to the floor. Leave for at least 5 minutes and then remove by scrubbing.
Settlement	N/A
Shelf-life/Storage	Many years if stored in original, tightly closed container in normal conditions. Do not store below 5°C. Protect from frost.
Hazards	Non-Flammable. Remove from skin with soap and water. Keep out of reach of children. A full Safety Data Sheet is available upon request.
Clean-Up	Clean equipment whilst wet with water.
Sizes	1lit

Rustins Limited, Waterloo Road, London NW2 7TX

February 2006

Telephone: 020 8450 4666 Fax: 020 8452 2008 Email: rustins@rustins.co.uk Web: www.rustins.co.uk