

 www.rustins.co.uk	<h2 style="text-align: center;">PRODUCT DATA SHEET</h2>
Product	<h3 style="text-align: center;">Linseed Oil</h3>
Type	Raw linseed oil.
Intended Use	Ideal for oiling Cricket bats, adding to paint and softening Metal Glazing Putty. Not suitable for oiling furniture or wooden floors. For furniture use Rustin's Danish Oil or Teak Oil . For floors use Rustin's Floor Oil .
Special Features	Pure and natural.
Preparation	Ensure surface to be oiled is clean and dry.
Application	Apply with a rag or brush and wipe off excess with a dry rag or cloth.
Coats	As required.
Drying Time	Slow drying. Dependant on temperature, humidity and film thickness. For faster drying linseed oil use Rustin's Boiled Oil .
Re-coating Time	Recoat once oil has dried.
Application Temp.	Ideally 15-25°C. Do not use below 15°C, or in conditions of high humidity.
Coverage	13-15 sq.m per litre, 1 coat, depending on the absorbency of the wood.
Maintenance	Re-oil periodically.
Compatibility	Compatible with most oil based products. Refer to manufacturer before mixing
Settlement	Stir thoroughly before use.
Shelf-life/Storage	The shelf life of the product in an airtight container is indefinite. It is preferable to store the product in a cool place. It is important to replace the lid and ensure an airtight seal.
Hazards	See Health & Safety data sheets.
Clean-Up	Clean brushes with White Spirit or Rustin's Brush Cleaner .
Sizes	125ml 250ml 500ml 2lit 4lit