

 www.rustins.co.uk	PRODUCT DATA SHEET
<i>Product</i>	Plastic Wood
<i>Type</i>	Quick drying wood filler.
<i>Intended Use</i>	For the repair of mouldings and broken edges, filling cracks and holes. Can be cut, filed, drilled and planed. When dry will take screws and nails.
<i>Special Features</i>	Can be used on wood, metal and stone. Available in; Natural, Teak, Mahogany, White.
<i>Preparation</i>	The surface must be cleaned and dry and for best adhesion slightly roughened.
<i>Application</i>	Apply in thin layers with applicator or filling knife. When hard apply further layers, making sure that the final application has is higher than the surrounding area. When plastic wood has hardened, sand smooth.
<i>Coats</i>	As many layers as required.
<i>Drying Time</i>	4-6 hours, deep holes may take longer.
<i>Application Temp.</i>	Ideally 15-25°C. Do not use below 5°C, or in conditions of high humidity.
<i>Compatibility</i>	Can be painted varnished or stained. Please be aware that when stained, colour may vary from surrounding wood.
<i>Settlement</i>	Stir thoroughly before use.
<i>Shelf-life/Storage</i>	The shelf life of the product in an airtight container is indefinite. It is preferable to store the product in a cool place. It is important to replace the lid and ensure an airtight seal.
<i>Hazards</i>	<p>Highly Flammable. Keep out of reach of children. Use only in well ventilated areas. Keep away from sources of ignition – no smoking. Avoid contact with skin and eyes. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvent or White Spirit.</p> A full health & safety data sheet is available on request.
<i>Clean-Up</i>	Clean tools with Cellulose Thinners.
<i>Sizes</i>	Tube 125ml tin