

July 2015

PRODUCT DATA SHEET

Product	Quick Dry Red Oxide Metal Primer				
Type	Metal primer.				
Intended Use	On all bare metal for interior and exterior use.				
Special Features	Quick drying and formulated with acrylic and special anti-corrosive pigments, to prevent corrosion.				
Preparation	The surface must be clean, smooth, sound, dry, free from wax, dust and contaminates. The bare metal should also be free from rust. Existing rust may be removed with Rustin's Rust Remover .				
Application	Use a good quality brush and apply evenly.				
Coats	1 coat is usually sufficient. A second coat may be applied if required. Sand lightly between coats if required.				
Drying Time	30 minutes depending on temperature and humidity.				
Re-coating Time	4 hours.				
Application Temp.	Ideally 15-25°C. Do not use below 10°C, or in conditions of high humidity or if rain imminent when using outdoors.				
Coverage	12-15 sq meters per litre per coat, depending on the absorbency of the surface.				
Maintenance	The surface may be cleaned with a mild detergent solution or White Spirit as necessary. Worn areas may be re-coated once cleaned and lightly sanded to provide a key.				
Compatibility	Must be over painted with an undercoat before application of top coat.				
Settlement	STIR WELL BEFORE USE.				
Shelf-life/Storage	Many years if stored in original tightly closed container in cool dry conditions.				
Hazards	Keep out of reach of children. Avoid contact with skin and eyes. After contact with skin, wash immediately with plenty of soap and water. A full Safety Data Sheet is available upon request or on www.rustins.co.uk				
Clean-Up	Remove excess product from brushes before cleaning in water. Hard brushes can be cleaned with Rustin's Brush Restorer.				
Sizes	250ml	500ml	1 litre	2.5 litre	5 litre